

HANGING STORAGE



SUPPLIES:

Fusible Fleece Batting
Bold Packed Floral Apparel Fabric
Mustard Mini Flower Apparel Fabric
Spa Washed Duck Cloth Fabric
Teal Washed Duck Cloth Fabric
Feuille De Citron Apparel Fabric
Corn Yellow Striped Slub Duck Cloth Fabric
Farmer's Leather Bundle
Brown Round Leather Cord Spool - 1mm
Midweight Fusible Interfacing

INSTRUCTIONS:

1. Cut main fabric, lining, fusible fleece and interfacing according to pattern.
2. With right sides of main fabric pieces facing, sew along 12 ½" and 8" edges with ¼" seam allowance. Press seams. Pin and sew box corners with ¼" seam allowance.
3. Iron fusible fleece to lining pieces according to package instructions. With right sides facing, sew along 12 ½" and 8" edges with ½" seam allowance. Press seams. Pin and sew box corners with ½" seam allowance. Place lining into outer main fabric layer.
4. Following package instructions, iron interfacing flush to one long edge of trim piece with ½" seam allowance around three sides. Turn exposed long edge over interfacing and iron. Top stitch. With right sides facing, join ends of trim piece to form a circle and sew together with ½" seam allowance.
5. Pin trim piece inside of bag with right sides facing and all seams matching. Sew all pieces together with ½" seam allowance. Fold trim over outside of bag. Sew trim across back of bag to secure fold.
6. With right sides facing, sew along long edge of strap piece with ¼" seam allowance. Press seam. Turn and press.
7. Trim leather piece to length of fabric strap. Layer fabric strap over leather, and use awl to punch four small holes at each end. Stitch through holes with leather cord to secure strap to bag.